

PRODUCT SPECIFICATION

Surface-mounted convertible automatic universal roll paper towel dispenser and waste receptacle, Bobrick Model B-3979.

Surface-mounted convertible automatic universal roll paper towel dispenser and waste receptacle shall be constructed entirely of type-304 stainless steel. Exposed surfaces shall have satin finish. Flange shall be 22-gauge (0.8mm) drawn, and beveled one-piece seamless construction. Door shall be 18-gauge (1.2mm) stainless steel and shall be secured to cabinet with full-length stainless steel piano-hinge and be equipped with a concealed tumbler lock. Automatic roll towel dispenser accommodates up to 8" (205mm) wide, 8" (205mm) diameter, nonperforated paper towel rolls, 800 ft (244 m) long. Dispenser automatically dispenses towel when hands are placed under the towel opening. Dispenser can be powered by 4 "D" size alkaline batteries or an optional 6 volt DC power supply. Equipped with switches that allow paper length to be set at 9" (230mm), 12" (305mm) or 15" (380mm), second activation delay that can be set at 1, 2, or 3 seconds, and "Paper Saver" feature that provides a shorter second sheet with options of 25% shorter and 12.5% shorter. Blinking LED indicates if batteries need to be replaced and, when plugged into the building main power, that the dispenser is powered and ready to function. Removable stainless steel waste receptacle shall be 8" (205mm) deep and secured to cabinet by tumbler lock; top and bottom edges shall be hemmed for safe handling. Minimum capacity: 12-gal. (45.5-L).

This unit is field convertible to:

- Folded Towel Dispenser Module: order Part No. 3944-52
- Mechanical (Non-Automatic) Universal Touch-Free Roll Towel Dispenser Module: order Part No. 3961-50
- 12-gallon Reusable Vinyl Liner: order Part No. 3944-12
- 18-gallon Waste Receptacle: order Part No. 368-60
- 18-gallon Reusable Vinyl Liner: order Part No. 368-16
- LinerMate™ for 12-gal waste only: order Part No. 3944-134

